



Connects2Vision

User Manual

CAM-32

Universal Reverse Camera ideal for
Van/Camper Vans

PRODUCT FEATURES:

Image Sensor: 1099 HD CCD

TV Lines: 560

Resolution: 976 x 496

Minimum Illumination: 0.1 Lux

TV System: NTSC

Waterproof Rating: IP68

Viewing Angle: 135 Degrees (Horizontal) 105 Degrees (Vertical)

Electronic Shutter: NTSC 1/60S, PAL 1/50S

Enhanced Performance In Low Light: Yes

Video Output: 1.0V p-p 75ohm

Operating Voltage: 12-24V DC (Negative Ground)

Current Consumption: 138.8 mA @ 13.8V

Operating Temperature: -20 Degrees C to +75 Degrees C

DISCLAIMER:

Prior to Installation

Read the manual prior to installation. Technical knowledge is necessary for installation. The place of installation must be free of moisture and away from heat sources. Please ensure you use the correct tools to avoid damage to the vehicle or product.

Connects2 can not be held responsible for the installation of this product.

Technical Support

Connects2 want to provide a fast and suitable resolution should you encounter any technical issues. With this in mind, when contacting Connects2, try to provide as much Information as possible. This will speed up the process and help us to help you.

Please use our dedicated online technical support centre: support.connects2.com

www.c2vision-eu.com

- Camera with 30cm connection cable
- Instructions

INSTALLATION

Note: CAM-RCA1 extension cable is required for installation.

1. Connect the Black wire to a suitable ground and the Red wire to a switched +12V supply.
2. If the camera is to be used in the rear of the vehicle, the Red wire should be connected to the reversing light circuit or an interface which provides a reverse signal.
3. Select a suitable location for the camera and ensure that the area is free from all cables, fuel & oil. Whenever possible, avoid locations that are subject to road dirt & water spray.
4. Mount the camera to the desired location and connect the CAM-RCA1 extension cable to the 30cm connection cable.
5. Connect the camera to the display screen via the Yellow RCA connector and ensure that the image is displayed correctly.
6. Adjustment of the camera may be required to ensure that the correct angle/orientation of the image is achieved.



Subscribe to our YouTube Channel for installation guides and tips... www.youtube.com/connects2