



Connects2Vision

User Manual

CAM-CT1

High Level Brake Light Reverse Camera
Citroen Dispatch, Jumpy, Spacetourer 2016>

PRODUCT FEATURES:

Image Sensor: 1/3" CMOS

TV Lines: 700

Resolution: 500 x 582

Minimum Illumination: 0 Lux

TV System: PAL

Waterproof Rating: IP69K

Viewing Angle: 170 Degree

Automatic Back Light Compensation

Mirror Image Available

Operating Voltage: 12V DC (Negative Ground)

Current Consumption: 37mA @ 13.8V

Operating Temperature: -30 Degrees C to +70 Degrees C

DISCLAIMER:

Prior to Installation

Read the manual prior to installation. Technical knowledge is necessary for installation. Please ensure you use the correct tools to avoid damage to the vehicle or product.

Connects2 can not be held responsible for the installation of this product.

Technical Support

Connects2 want to provide a fast and suitable resolution should you encounter any technical issues. With this in mind, when contacting Connects2, try to provide as much Information as possible. This will speed up the process and help us to help you.

Please use our dedicated online technical support centre: support.connects2.com

www.c2vision-eu.com

- 1m Camera with cable to mini Male 4pin connector
- 20cm camera connection cable with mini Female 4pin connector to Male 4 pin 'screw on' connector
- 10m Female 4 pin 'screw on' connector to Male Video RCA plus 12V+ & Ground wire connections for power
- Instructions

INSTALLATION

1. Remove the relevant brake light housing from the vehicle and carefully remove the bulbs/bulb holder assembly.
2. Insert the bulbs/bulb holder assembly into the camera and refit to the vehicle taking care not to trap any cables.
3. Connect the camera cable to the camera connection cable.
4. Connect the camera connection cable to the display monitor using an extension - 4pin to RCA convertor cable and ensure that the image is displayed correctly.



Subscribe to our YouTube Channel for installation guides and tips... www.youtube.com/connects2