



Connects2Vision

User Manual

CAM-IV2

Iveco Reverse Camera
Iveco Daily 2014>

PRODUCT FEATURES:

Image Sensor: 1/3" CCD

TV Lines: 700

Resolution: 976 x 494 (NTSC) 976 x 582 (PAL)

Minimum Illumination: 0 Lux

TV System: NTSC/PAL

Waterproof Rating: IP68

Infra-Red LED's: Yes

Night Vision Distance: 35ft

Viewing Angle: 170 Degrees

Image: Mirror

Enhanced Performance In Low Light: Yes

Operating Voltage: 12V DC (Negative Ground)

Current Consumption: 77-125mA @ 13.8V

Operating Temperature: -20 Degrees C to +70 Degrees C

DISCLAIMER:

Prior to Installation

Read the manual prior to installation. Technical knowledge is necessary for installation. Please ensure you use the correct tools to avoid damage to the vehicle or product.

Connects2 can not be held responsible for the installation of this product.

Technical Support

Connects2 want to provide a fast and suitable resolution should you encounter any technical issues. With this in mind, when contacting Connects2, try to provide as much Information as possible. This will speed up the process and help us to help you.

Please use our dedicated online technical support centre: support.connects2.com

www.c2vision-eu.com

- Camera with 70cm cable to Male 4pin camera connector
- 10m 4pin to 4pin extension cable
- Camera connection cable with Female 4pin camera connector, 2x RCA Female connectors and Female DC connector
- 1.45 DC power cable with Male DC connector
- Male to Male RCA splice
- Instructions

INSTALLATION

1. Remove the third brake light housing from the vehicle and remove the brake light assembly and courtesy lamp.
2. Attach the brake light assembly and courtesy lamp to the CAM-IV2 and refit to the vehicle taking care not to trap any cables.
3. Connect the Black wire to a suitable ground and connect the Red wire to the reversing light circuit or an interface which provides a reverse signal.
4. Connect the camera to the 4pin extension cable, connect the extension cable to the camera connection cable and connect the camera connection cable to the display screen via the Yellow RCA connector and supplied RCA splice and ensure that the image is displayed correctly.



Subscribe to our YouTube Channel for installation guides and tips... www.youtube.com/connects2