




adaptiv*mini*

Now with dynamic parking lines



Adaptiv Mini Fitting & User Guide

CAM-MB6-AD

WWW.ADAPTIV-MULTIMEDIA.COM

Adaptiv Mini

Adaptiv Mini allows HDMI & Camera input to the OEM screen. Includes dynamic parking guidelines



HDMI INPUT



**FRONT & REAR
CAMERA**

This plug and play Mini interface adds HDMI to connect your Apple or Android device, allowing you to mirror your smartphone display on the vehicle's original screen. Inputs for front and rear aftermarket cameras also come as standard with the Mini.

Application

For Mercedes-Benz vehicles with NTG 4.5 with 5.8" & 6.5" display.

Kit Includes

Adaptiv Interface
Vehicle Harness


Prior to installation

Read the manual prior to installation. Technical knowledge is necessary for installation. The place of installation must be free of moisture and away from heat sources. Connects2 cannot be held responsible for the installation of this product.

Technical Support


Connects2 want to provide a fast and suitable resolution should you encounter any technical issues. With this in mind, when contacting Connects2, try to provide as much Information as possible. This will speed up the process and help us to help you.

Please use our dedicated online technical support centre: support.connects2.com




NOTE:
All connections are made at the rear of the OEM head unit. No connections need to be made directly to the display.


DIP SWITCH SETTINGS




DIP 1
If the vehicle has OEM reverse camera (ON: YES OFF: NO)



DIP 3
If the vehicle has after-market reverse camera (ON: YES OFF: NO)



DIP 2
If the vehicle has after-market front camera (ON: YES OFF:NO)



DIP 4
5.8" display - ON
6.5" display - OFF
DIP 5
OFF



Button Config

Button 1 - Back/Back Arrow

HDMI Access

Select Aux In from the OEM source menu.

Hold **BUTTON 1** for 2 seconds to switch between OEM screen and Adaptiv Mini HDMI screen. Double press **BUTTON 1** to exit.



Video In Motion Warning - 10 MPH

Double Press **BUTTON 1** to disable the video in motion warning message

Rear and Front Camera Access

From either HDMI mode or OEM mode

1. Select reverse gear for reverse camera
 2. Deselect reverse gear - will go to after market front camera (if DIP 2 ON)
- Double Press **BUTTON 1** to cancel front camera or drive over 10 MPH



Front Camera Access

Double Press **BUTTON 1** to enter the front camera screen (if DIP 2 is ON). Double press **BUTTON 1** to exit.

View Version Number

Hold **BUTTON 1** for 8 seconds to enter firmware information screen

Toggle Parking Guidelines On/Off

Hold **BUTTON 1** for 2 seconds whilst the camera image is displayed on screen