



Connects2Vision

User Manual

CAM-NS4-AD Reverse Camera Add On Interface For select Nissan vehicles

APPLICATION:

Nissan Navara (D23)	2016 - 2019
Nissan NP300 (D23)	2016 - 2019
Nissan Note	2013 - 2018
Nissan NV200	2010 >
Nissan NV300	2014 >
Nissan Qashqai (J11)	2014 - 2017
Nissan X-Trail (T32)	2014 - 2017

Allows for the addition of an aftermarket reverse camera to the original vehicle screen. This harness works with models which feature factory Nissan multimedia systems without navigation.

Note: the camera being paired with this product must be NTSC.

DISCLAIMER:

Prior to Installation

Read the manual prior to installation. Technical knowledge is necessary for installation. The place of installation must be free of moisture and away from heat sources. Please ensure you use the correct tools to avoid damage to the vehicle or product.

Connects2 can not be held responsible for the installation of this product.

Technical Support

Connects2 want to provide a fast and suitable resolution should you encounter any technical issues. With this in mind, when contacting Connects2, try to provide as much Information as possible. This will speed up the process and help us to help you.

Please use our dedicated online technical support centre: support.connects2.com

- Reverse Camera Add On Adapter
- 3x Male Bullet Connectors
- Instructions

INSTALLATION

1. Remove the vehicles head unit by following the manufacturer's instructions/guidelines. Once removed, disconnect all the power connections including the 32-pin connector.

2. With the aftermarket camera installed, connect the cameras RCA to the yellow RCA of the CAM-NS4-AD.

3. Connect the single grey cable labelled 'REV' to a source of reverse. A typical source would be the reversing lights circuit if there is not a specific connection behind the head unit.

4. Connect the red & black 6V wires if the camera being used needs an 6V power supply.

Note: if installing a 12V camera, this will need to be powered by an alternative fused, ignition live 12V power supply from the vehicle.

5. Attach the 32-pin specific connector to the back of the head unit. When done, connect the power and test the reverse camera's functionality before reassembling the dashboard.



Subscribe to our YouTube Channel for installation guides and tips... www.youtube.com/connects2