



...connecting to the aftermarket

Connects2Vision

User Manual

CAM-NUMBERPLATE-3 Number Plate Mounted Camera

PRODUCT FEATURES:

Image Sensor: 1099 HD CCD

Resolution: 976 x 496

TV Lines: 480

Lumen: 0.1 Lux

Video Output: 1.0V p-p 75ohm

Operating Voltage: 12V DC (Negative Ground)

Current Consumption: >125mA @ 13.8V

Operating Temperature: -20 Degrees C to +70 Degrees C

Horizontal Angle: 170 Degrees

Vertical Angle: 120 Degrees

Waterproof Rating: IP68

TV System: NTSC/PAL

Parking Lines: Yes

Removable Lines: Yes

Image Adjustment: Yes (Mirror/Normal)

Infra-Red LED's: Yes

DISCLAIMER:

Prior to Installation

Read the manual prior to installation. Technical knowledge is necessary for installation. Please ensure you use the correct tools to avoid damage to the vehicle or product.

Connects2 can not be held responsible for the installation of this product.

Technical Support

Connects2 want to provide a fast and suitable resolution should you encounter any technical issues. With this in mind, when contacting Connects2, try to provide as much information as possible. This will speed up the process and help us to help you.

Please use our dedicated online technical support centre: support.connects2.com

- Camera with mounting plate and 1m camera cable to mini Male 6pin connector
- Camera connection cable with mini Female 6pin connector, RCA Female connector and 1m DC power cable
- 6m RCA Male to Male extension cable
- Instructions

INSTALLATION

1. Connect the Black wire to a suitable ground and the Red wire to a switched +12V supply.
2. If the camera is to be used in the rear of the vehicle, the Red wire should be connected to the reversing light circuit or an interface which provides a reverse signal.
3. Select a suitable location for the camera and ensure that the area is free from all cables, fuel & oil.
4. Whenever possible, avoid locations that are subject to road dirt & water spray.
5. Mount the camera in the desired location using the supplied mounting plate.
6. Using the supplied video cable, connect the camera to the display screen and ensure that the image is displayed correctly.
7. Adjustment of the camera may be required to ensure that the correct angle of the image is achieved.
8. To remove the parking line feature, cut the small Green looped wire located on the camera connection cable.
9. To swap the image from mirror to normal, cut the small White looped wire located on the camera connection cable.



Subscribe to our YouTube Channel for installation guides and tips... www.youtube.com/connects2