



Connects2Vision

User Manual

RVM5-CVBS

5" Digital TFT LCD Colour Monitor

PRODUCT FEATURES:

5" TFT LCD colour monitor with AV signal auto detect switch-on, reverse signal sensing switch-on, integrated stand and 2x video inputs.

- Display Format: 16:9
- TV System: PAL/NTSC (auto switch)
- Pixels: 1200 x 680
- Contrast: 350:1
- Operating Temperature: -20°C to +60°C
- Storage Temperature: -40°C to +85°C
- Operating Voltage: 9V-16V DC (Negative Ground)
- Power Supply: 12V DC

DISCLAIMER:

Prior to Installation

Read the manual prior to installation. Technical knowledge is necessary for installation. Please ensure you use the correct tools to avoid damage to the vehicle or product.

Connects2 can not be held responsible for the installation of this product.

Technical Support

Connects2 want to provide a fast and suitable resolution should you encounter any technical issues. With this in mind, when contacting Connects2, try to provide as much Information as possible. This will speed up the process and help us to help you.

Please use our dedicated online technical support centre: support.connects2.com

CONTENTS

- Screen with stand and 45cm connection cable to 2x RCA Female connectors and Female DC connector
- DC power connector with Male DC connector
- Instructions

INSTALLATION

Front & rear camera example

1. Connect the Black wire to a suitable ground and the Red wire to a switched +12V supply.
2. Connect the Yellow RCA Female connector (AV1) to the front camera and the White RCA Female connector (AV2) to the reversing camera.
3. When the reversing camera is triggered, the screen automatically switches to AV2. When no signal is received from both front and rear cameras, the monitor will go into stand-by mode.



Subscribe to our YouTube Channel for installation guides and tips... www.youtube.com/connects2